


SGC | Sand and Gravel Crusher

Small Aggregates



General Features


- Gentle crushing through slow roller rotation
- Rollers mechanically synchronized
- Hydraulic adjustment of the roller gap
- Hydraulic overload protection
- High coarse particle content and low fines in the end product
- Low oversize content
- Energy efficient
- Wear Resistant
- Low maintenance costs
- Application-specific design of crusher rollers

Application data

- Natural stone: gravel and crushed stone
- Recycled material: concrete, rubble, asphalt
- Incineration slag/bottom ash
- Capacity 30-400t/h
- Crushing ratio 1:2 – 1:4
- Efficient production of final aggregates <16mm
- Production of coarse sand in a closed loop system

SGC | Sand and Gravel Crusher

Sizes and Application



A: Axle distance | B: roller length | C: Machine width | D: Machine length | E: Machine height

Size	Weight t	Throughput ¹ t/h	F100 mm	P90 mm	A mm	B mm	C mm	D mm	E mm	
SGC 650 -08	10	100	80	0-8	650	800	2150	3000	950	
SGC 650 -11	12	200	80	0-8	650	1100	2400	3000	950	
SGC 800 -12	18	300	100	0-8	800	1200	2500	3600	1250	
SGC 1000 -13	23	420	120	0-8	1000	1300	2750	3850	1400	
SGC 1200 -14	28	600	120	0-8	1200	1400	3000	4300	1800	

¹Throughput calculation based on a material density of 2 kg/l.

Crush + Size Technology GmbH & Co. KG

Kölner Straße 94 | D-51702 Bergneustadt | +49(0)2261 80 47 300 | sales@crush-size.de | www.crush-size.de